



X - Height of the gliding support

For planning purposes, please consider the height of the gliding supports (X) if usage is demanded.

All dimensions in mm

Position		1	2	3	4	5	Distance				
for Pipe d	Item No. hot-dip galvanized	H	Angle	2 x Gusset plate				Pipe clamp according to DIN 3567 A	Screws DIN 933	Hexagon nut DIN 934	e
				b	s	a	c				
168.3	24034552	185	L120x80x8	60	6	132	32	50x8.0	M16x45	M16	22
219.1	24034848	218	L120x80x8	60	6	132	40	50x8.0	M16x45	M16	22
273.0	24034849	245	L150x75x9	80	8	218	20	60x8.0	M20x50	M20	26
323.9	24034553	270	L150x75x9	80	8	241	20	60x8.0	M20x50	M20	26
355.6	24035436	286	L150x75x9	80	8	254	20	60x8.0	M20x50	M20	26
406.4	24034792	313	L150x75x9	80	8	276	21	80x8.0	M24x60	M24	36
508.0	24035437	372	L180x90x10	100	10	360	10	80x8.0	M24x60	M24	35
610.0	24036058	423	L180x90x10	100	10	395	10	80x8.0	M24x60	M24	35

Other diameters and A-dimensions on request. Please provide the requested pipe diameter and the A-dimension.

Specification

Material No. 1.0038, galvanized or hot-dip galvanized.

Also deliverable in ordinary steel or stainless steel material No. 1.4301 and 1.4571.

Other materials on request.

**Also STAINLESS available
RUST
PROOF**



Ordering designations: Type... Diameter... H-dimension... Surface... Item number
e. g. 185 ø219.1 H=218 hot dip galvanized 24034848